

# SAFETY DATA SHEET

## Lock De-icer

Version: 2.1

Update:11/13/2014

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

**Product name** Lock Deicer  
**Product No.** 00500-V; 05002-V; 00502-V; 00500-VCS12; 00500-VFB24

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Lock Deicer

#### 1.3. Details of the supplier of the safety data sheet

**Importer** Bell Automotive Products, Inc.  
18940 N. Pima Road, Suite 200 Scottsdale, AZ 85255  
Tel: 888.694.2355  
Fax:480.991.5595  
rlee@bellautomotive.com

**Manufacture** Shieun Ta Industry CO.,Ltd.  
No.34-12,Lane194,Chung Cheng 3<sup>rd</sup> Rd,Ying Ko District  
New Taipei City,Taiwan.  
Tel: + 886 2 2670 7931  
Fax:+ 886 2 2670 7914  
shieun-ta@umail.hinet.net

#### 1.4. Emergency telephone number

USA: 888.694.2355  
International +886 2 2670 793

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Flammable aerosols, Category 2  
Eye irritation, Category 2A

#### 2.2. Label elements

**Symbol:** GHS02  , GHS07 

**Signal word:** Danger

#### **Hazard statements:**

Extremely flammable aerosols.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

**SAFETY DATA SHEET**  
**Lock De-Icer**

Version: 2.1  
Update:11/13/2014

**Precautionary statements:**

**General precautionary statements**

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

**Prevention precautionary statements**

Keep away from heat, hot surfaces, open flames, sparks. - No smoking.

Avoid breathing mist, spray, vapours.

Use only outdoors or in a well-ventilated area.

**Response precautionary statements**

IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes.

IF EYES IRRITATION PERSISTS: Get medical advice/attention.

**Storage precautionary statements**

Store in a well ventilated place.

Store at temperatures not exceeding 50°C/122°F

Do not expose to temperatures exceeding 50 °C/122 °F




**Disposal precautionary statements**

Dispose of contents/container to comply with local, state and federal regulations.

**2.3. Other hazards**

No data available.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Identification	Name	Classification	w/w %
CAS: 67-63-0 EC : 200-661-7	Isopropyl Alcohol	 Flam. Liq.2, H225  Eye Irrit.2, H319; STOT SE3, H336	95.0 ~ 97.0
CAS:8042-47-5 EC :232-455-8		Mineral Oil	
CAS: 124-38-9 EC : 204-696-9	Carbon Dioxide	 Press. Gas; H280	1.0 ~ 5.0
<b>Total</b>		<b>100.0</b>	

**The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.**

**SAFETY DATA SHEET**  
**Lock De-Icer**

Version: 2.1  
Update:11/13/2014

**SECTION 4 : FIRST AID MEASURES**

**4.1. Description of first aid measures**

**First-aid measures general**

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Never give alcohol to drink.

**First-aid measures after inhalation**

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

**First-aid measures after skin contact**

Rinse with water. Soap may be used. Do not apply (chemical) neutralizing agents. Take victim to a doctor if irritation persists.

**First-aid measures after eye contact**

Rinse immediately with plenty of water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

**First-aid measures after ingestion**

Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Give activated charcoal. Call Poison Information Centre. Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital. Doctor: gastric lavage.

**4.2. Most important symptoms and effects, both acute and delayed**

**Symptoms/injuries after inhalation**

EXPOSURE TO HIGH CONCENTRATIONS: Coughing. Dry/sore throat. Central nervous system depression. Dizziness. Headache. Narcosis.

**Symptoms/injuries after skin contact**

Dry skin.

**Symptoms/injuries after eye contact**

Irritation of the eye tissue

**Symptoms/injuries after ingestion**

AFTER ABSORPTION OF HIGH QUANTITIES: Central nervous system depression. Headache. Dilation of the blood vessels. Low arterial pressure. Nausea. Vomiting. Abdominal pain. Disturbed motor response. Disturbances of consciousness. FOLLOWING SYMPTOMS MAY APPEAR LATER: Body temperature fall. Slowing respiration.

**Chronic symptoms**

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Dry skin. Itching. Cracking of the skin. Skin rash/inflammation. Impaired memory.

**SAFETY DATA SHEET**  
**Lock De-Icer**

Version: 2.1  
Update:11/13/2014

**4.3. Indication of any immediate medical attention and special treatment needed**

No additional information available.

**SECTION 5 : FIRE-FIGHTING MEASURES**

**5.1. Extinguishing media**

**Extinguishing media**

Use: Foam, carbon dioxide or dry powder.

**Unsuitable extinguishing media**

Do not use water jet as an extinguisher.

**5.2. Special hazards arising from the substance or mixture**

**Hazardous combustion products**

During fire, toxic gases (CO, CO<sub>2</sub>) are formed.

**Unusual Fire & Explosion Hazards**

Extremely flammable. Aerosol cans may explode in a fire.

**Specific hazards**

When heated and in case of fire, harmful vapours/gases may be formed.

**5.3. Advice for fire-fighters**

**Special Fire Fighting Procedures**

Cool containers exposed to flames with water until well after the fire is out.

**Protective equipment for fire-fighters**

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

**6.1.1. For non-emergency personnel**

**Protective equipment**      Gloves. Protective goggles.

**Emergency procedures**      Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. No smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Use non-sparking tools.

**6.1.2. For emergency responders**

**Protective equipment**      Equip cleanup crew with proper protection. Do not breathe gas, fumes, vapour or spray.

**Emergency procedures**      Stop leak if safe to do so. Ventilate area. If a major spill occurs, all personnel should be immediately evacuated and the area ventilated.

**6.2. Environmental precautions**

# SAFETY DATA SHEET

## Lock De-Icer

Version: 2.1

Update:11/13/2014

Prevent spreading in sewers.

### **6.3. Methods and material for containment and cleaning up**

**For containment** Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Dam up the liquid spill. Try to reduce evaporation. Dilute/disperse combustible gas/vapour with water curtain. Provide equipment/receptacles with earthing.

**Methods for cleaning up** Take up liquid spill into absorbent material, e.g.: dry sand/earth/vermiculite or powdered limestone. Do not use compressed air for pumping over spills. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.

### **6.4. Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

Provide good ventilation. Avoid contact with eyes. Wash hands after handling.

### **7.2. Conditions for safe storage, including any incompatibilities**

Keep away from heat, sparks and open flame. Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### **7.3. Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **8.1. Control parameters**

Isopropyl Alcohol (67-63-0)			
USA ACGIH TWA	USA ACGIH STEL	OSHA PEL (TWA)	OSHA PEL (TWA)
200 ppm	400 ppm	980 mg/m <sup>3</sup>	400 ppm

### **8.2. Exposure controls**

#### **Engineering measures**

Provide adequate ventilation.


#### **Personal protective equipment**

Gloves. Safety glasses. Avoid all unnecessary exposure.

# SAFETY DATA SHEET

## Lock De-Icer

Version: 2.1  
Update:11/13/2014



### Hand protection

For prolonged or repeated skin contact use suitable protective gloves.

### Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

### Respiratory protection

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

THIS PRODUCT IS A COLORLESS LIQUID IN A PRESSURIZED CAN (AEROSOL CAN), WITH CARBON DIOXIDE AS A PROPELLANT. THE FOLLOWING VALUES ARE FOR THE MAIN COMPONENT—ISOPROPYL ALCOHOL (67-63-0)

**Appearance** : Clear liquid.

**Odor** : Alcohol odor

**Specific Gravity** : 0.786

**Ph as supplied** : N/A

**Boiling Point (°F)** : 180 (AT 760 mm Hg. )

**Melting Point(°F)** : -127

**Flash point** : 12 °C

**Evaporation Rate (n-Butyl Acetate=1)** : 1.5

**Vapor Pressure (mm Hg):** 33 (AT 68 °F )

**Vapor Density (AIR=1)** : 2.1

**Solubility in Water** : Miscible.

### 9.2 Other information

**VOC content:** > 96 %

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

No specific reactivity hazards associated with this product.

### 10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

### 10.3. Possibility of hazardous reactions

# SAFETY DATA SHEET

## Lock De-Icer

Version: 2.1  
Update:11/13/2014

### Hazardous Polymerisation

Will not polymerise.

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

None under normal conditions.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### Acute toxicity

Isopropyl Alcohol ( 67-63-0)	
LD50 oral rat	5045 mg/kg (Rat)
LD50 dermal rabbit	12870 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	73 mg/l/4h (Rat)
Mineral Oil (8042-47-5)	
LD50 oral rat	Not available
LD50 dermal rabbit	Not available
LC50 inhalation rat (mg/l)	Not available
Carbon Dioxide (124-38-9)	
LD50 oral rat	Not available
LD50 dermal rabbit	Not available
LC50 inhalation rat (mg/l)	Not available

<b>Skin corrosion/irritation</b>	Not classified
<b>Serious eye damage/irritation</b>	Causes eye irritation.
<b>Respiratory or skin sensitization</b>	Not classified
<b>Germ cell mutagenicity</b>	Not classified
<b>Carcinogenicity</b>	Not classified
<b>Reproductive toxicity</b>	Not classified
<b>Symptoms/injuries after inhalation</b>	EXPOSURE TO HIGH CONCENTRATIONS: Coughing. Dry/sore throat. Central nervous system depression. Dizziness. Headache. Narcosis.
<b>Symptoms/injuries after skin contact</b>	Dry skin.
<b>Symptoms/injuries after eye contact</b>	Irritation of the eye tissue.
<b>Symptoms/injuries after ingestion</b>	AFTER ABSORPTION OF HIGH QUANTITIES: Central nervous system depression.

# SAFETY DATA SHEET

## Lock De-Icer

Version: 2.1

Update:11/13/2014

Headache. Dilation of the blood vessels. Low arterial pressure. Nausea. Vomiting. Abdominal pain. Disturbed motor response. Disturbances of consciousness. FOLLOWING SYMPTOMS MAY APPEAR LATER: Body temperature fall. Slowing respiration.

### Chronic symptoms

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Dry skin. Itching. Cracking of the skin. Skin rash/inflammation. Impaired memory.

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

This product is not expected to be hazardous to the environment.

#### 12.1. Toxicity

**Ecology – general** Not available.

**Ecology – air** Not available.

**Ecology – water** Ground water pollutant. Not harmful to fishes (LC50(96h) >1000 mg/l). Not harmful to invertebrates (Daphnia) (EC50 (48h) > 1000 mg/l). Not harmful to algae (EC50 (72h) >1000 mg/l).

Isopropyl Alcohol ( 67-63-0)	
LC50 fishes 1	4200 mg/l (96 h; Rasbora heteromorpha; Flow-through system)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna)
LC50 fish 2	9640 mg/l (96 h; Pimephales promelas; Lethal)
EC50 Daphnia 2	13299 mg/l (48 h; Daphnia magna)
Threshold limit algae 1	> 1000 mg/l (72 h; Scenedesmus subspicatus; Growth rate)
Threshold limit algae 2	1800 mg/l (72 h; Algae; Cell numbers)
Mineral Oil (8042-47-5)	Not available
Carbon Dioxide (124-38-9)	Not available

#### 12.2. Persistence and degradability

Isopropyl Alcohol ( 67-63-0)	
<b>Persistence and degradability</b>	Readily biodegradable in water. Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. No (test)data on mobility of the substance available.
<b>Biochemical oxygen demand (BOD)</b>	1.19 g O <sup>2</sup> /g substance
<b>Chemical oxygen demand (COD)</b>	2.23 g O <sup>2</sup> /g substance
<b>ThOD</b>	2.40 g O <sup>2</sup> /g substance
<b>BOD (% of ThOD)</b>	0.49 % ThOD



**SAFETY DATA SHEET**  
**Lock De-Icer**

Version: 2.1  
Update:11/13/2014

**12.3. Bioaccumulative potential**

<b>Isopropyl Alcohol ( 67-63-0)</b>	
Log Pow	0.05 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

<b>Mineral Oil (8042-47-5)</b>	Not available
--------------------------------	---------------

<b>Carbon Dioxide (124-38-9)</b>	Not available
----------------------------------	---------------

**12.4. Mobility in soil**

No further relevant information available.

**12.5. Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6. Other adverse effects**

Not determined.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Recover and reclaim or recycle, if practical.

**SECTION 14: TRANSPORT INFORMATION**

**14.1. UN number**

UN No. (ADR/RID/ADN) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

**14.2. UN proper shipping name**

**Proper Shipping Name** AEROSOLS

**14.3. Transport hazard class(es)**

ADR/RID/ADN Class 2

ADR/RID/ADN Class Class 2: Gases

ADR Label No.: 2.1

IMDG Class: 2

ICAO Class/Division: 2.1

**SAFETY DATA SHEET**  
**Lock De-Icer**

Version: 2.1  
Update:11/13/2014

Transport Label(s):



**14.4. Packing group**

Packing Group II – medium danger

**14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant: No.

**14.6. Special precautions for user**

EmS (Emergency Schedules) Code: F-D, S-U

Tunnel Restriction Code: (D)

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

**SECTION 15: REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**U.S. Federal regulations:**

All ingredients of this product are listed, or are exempt from listing on the TSCA inventory. Export notification is required under TSCA sec 12-B.

Regulatory status of hazardous chemical constituents of this product :

Ingredient	Extremely Hazardous*	Toxic Chemical**	12B Export Notification
ISOPROPYL ALCOHOL 67-63-0	NO	NO	REQUIRED
CARBON DIOXIDE 124-38-9	NO	NO	NOT REQUIRED
WHITE MINERAL OIL 8042-47-5	NO	NO	NOT REQUIRED

\*Consult the appropriate regulations for emergency planning and release reporting requirements for substances on the SARA Section 301 Extremely Hazardous Substance List.

\*\*Substances for which the "Toxic Chemical" column is marked "Yes" are on the SARA Section 313 list of Toxic Chemicals, for which release reporting may be required. For specific requirements, consult the appropriate regulations.

**Superfund Amendments Reauthorization Act (SARA) Title III:**

# SAFETY DATA SHEET

## Lock De-Icer

Version: 2.1

Update:11/13/2014

Section 302 Extremely Hazardous Substances (EHS): None  
Section 311/312 Hazard Categories: Fire Hazard -- Yes  
Reactive Hazard -- No  
Release of Pressure -- Yes

### California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

### State Right to Know:

Rhode Island, Pennsylvania, Florida, Minnesota, Massachusetts, New Jersey, Tennessee, Illinois.

Name	CAS No.
Isopropyl Alcohol	67-63-0
Mineral Oil	8042-47-5
Carbon Dioxide	124-38-9

### Canadian regulations:

#### Canadian DSL/NDSL inventory status :

The components of this product are on the DSL inventory.

#### Canadian environmental Protection Act (CEPA) priorities substances lists :

The components of this product are not on the (CEPA) priorities lists.

#### Canadian WHMIS classification and symbols:

Class A : Compressed gas

Class B5 : Flammable Aerosols

Class D2B: Skin or eye irritation

### 15.2. Chemical Safety Assessment

Not applicable, this product is a mixture.

## SECTION 16: OTHER INFORMATION

### General information

AEROSOL CAUTION: Pressurised container. Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep out of the reach of children. Keep away from sources of ignition - no smoking.

### Safety Data Sheet Status

Revision Date: NOV-13-2014

### Risk Phrases In Full

R11 Highly flammable.

R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.

# SAFETY DATA SHEET

## Lock De-Icer

Version: 2.1  
Update:11/13/2014



### Hazard Statements In Full

H222	Extremely flammable aerosols.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
STOT SE 3	Specific Target Organ Toxicity Single exposure, Category 3, Narcosis

### NFPA Rating:

NFPA health hazard	<b>1</b> - Exposure could cause irritation but only minor residual injury even if no treatment is given.
NFPA fire hazard	<b>3</b> - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	<b>0</b> - Normally stable, even under fire exposure conditions, and are not reactive with water.

### HMIS Classification:

Health	<b>1</b> Slight Hazard - Irritation or minor reversible injury possible
Flammability	<b>3</b> Serious Hazard
Physical	<b>0</b> Minimal Hazard
Personal Protection	<b>B</b>   Safety Glasses      Gloves

### Disclaimer of liability

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and the manufacturer/distributor assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.