



SAFETY DATA SHEET

Revision Date 15-Sep-2017

Version 6

1. IDENTIFICATION

Product identifier

Product Name 133K ANTI-SEIZE LUBRICANT 8OZ

Other means of identification

Product Code 80078

Recommended use of the chemical and restrictions on use

Recommended Use Lubricant.

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
6875 Parkland Blvd.
Solon, OH 44139 USA

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

24-hour emergency phone number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral

Category 4

Label elements

Emergency Overview

Signal word

Warning

Harmful if swallowed



Appearance Silver	Physical state Paste	Odor Petroleum
--------------------------	-----------------------------	-----------------------

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product

Precautionary Statements - Response

Get medical advice/attention if you feel unwell
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
Rinse mouth

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Note L: The classification as a carcinogen 1 does not apply. The substance contains less than 3 % DMSO extract as measured by IP 346. This note applies only to certain complex oil derived substances in Annex I

Unknown acute toxicity 19.23275 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS**Substance(s)**

Chemical Name	CAS No	Weight-%
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC	64742-52-5	30 - 60
ALUMINIUM POWDER	7429-90-5	5 - 10
PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED LIGHT	64742-71-8	3 - 7

Any concentration shown as a range is due to batch variation.

4. FIRST AID MEASURES**Description of first aid measures****General advice**

Get medical advice/attention if you feel unwell.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin contact

IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse.

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.

Ingestion

IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider

Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

Water.

Specific hazards arising from the chemical

None in particular.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials Strong oxidizing agents, Acids, Alkalis, Amines

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ALUMINIUM POWDER 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust TWA: 5 mg/m ³ Al

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls**Engineering Controls**

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tight sealing safety goggles.

Skin and body protection

Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

Respiratory protection

Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties**Physical state**

Paste

Appearance

Silver

Odor

Petroleum

Odor threshold

No information available

Property**Values****Remarks • Method****pH**

No information available

Melting point / freezing point

No information available

Boiling point / boiling range

No information available

Flash point

> 93 °C / > 200 °F

Tag Closed Cup

Evaporation rate

< 1

Butyl acetate = 1

Flammability (solid, gas)

No information available

Flammability Limit in Air**Upper flammability limit:**

No information available

Lower flammability limit:

No information available

Vapor pressure

<5 mm Hg

Vapor density

>1

Air = 1

Relative density

1.17

Water solubility

Negligible

Solubility in other solvents

No information available

Partition coefficient

No information available

Autoignition temperature

No information available

Decomposition temperature

No information available

Kinematic viscosity

No information available

Dynamic viscosity

No information available

Explosive properties

No information available

Oxidizing properties No information available

Other Information

Softening point No information available

Molecular weight No information available

VOC Content (%) 0

Density No information available

Bulk density No information available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents, Acids, Alkalis, Amines

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis.
Ingestion	Harmful if swallowed.

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC 64742-52-5	A2	Group 1	Known	X
PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED LIGHT 64742-71-8	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)
A2 - Suspected Human Carcinogen
IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Not classifiable as a human carcinogen
NTP (National Toxicology Program)
Known - Known Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Target Organ Effects Central Vascular System (CVS), Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1978 mg/kg
ATEmix (inhalation-vapor) 32255 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

32.42995 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ALUMINIUM POWDER 7429-90-5	Ignitable powder

14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated

IATA

Proper shipping name: Not regulated

IMDG

Proper shipping name: Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
ALUMINIUM POWDER - 7429-90-5	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
CALCIUM OXIDE 1305-78-8	X	X	X
GRAPHITE 7782-42-5	X	X	X
ALUMINIUM POWDER 7429-90-5	X	X	X
PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED LIGHT 64742-71-8	-	X	-

COPPER 7440-50-8	X	X	X
---------------------	---	---	---

U.S. EPA Label Information**EPA Pesticide Registration Number** Not applicable**WHMIS Hazard Class**

D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 2	Flammability 1	Instability 0	-
<u>HMIS</u>	Health hazards 2	Flammability 1	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Revision Date 15-Sep-2017**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet